

HO-400 / HO-400R

INDIRECT FIRED SPACE HEATER



INFORMATION SHEET

FEATURES

- Diesel, oil, or kerosene
- Heated fuel filter
- 110% steel secondary containment
- Fully welded 16 ga 304 stainless steel heat exchanger
- Body panels made of 16 ga carbon steel with chip-resistant powder coating
- Flat-free tires with reinforced hubs
- Optional 60 or 118 US gal (227 or 447 l) fuel tank
- Riello burner



SPECIFICATIONS

	HO-400	HO-400R
BTUH	325,000 - 390,000 BTUH 95 - 114 kW	325,000 - 390,000 BTUH 95 - 114 kW
Air Movement	2,400 CFM 68 m ³ /min	3,500 CFM 99 m ³ /min
Weight	580 lbs 263 kg	600 lbs 272 kg
Dimensions	70" x 30" x 52" 178 x 76 x 132 cm	70" x 30" x 55" 178 x 76 x 140 cm
Power Supply	120 V / 15 A	120 V / 15 A
Current Draw	9 A	8 A
Ducting Capability	50' max 15 m max	100' max 30 m max
Recirculating	No	Up to 50' Up to 15 m
Certification	cETLus	cETLus
Fuel Tank Capacity	48 US gal 182 l	48 US gal 182 l
Run Time	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr
Fan Power	3/4 hp 0.55 kW	1 hp 0.74 kW
Thermostat	Yes	Yes